

DOMESTIC & COMMERCIAL ALUMINIUM ROLLER SHUTTERS

CSS90-Aluminium (Open link type)

Usage: Internal use only on shopfronts. Very tight coiling makes CSS90 particularly suitable for bar/kiosk and commercial applications where permanent vision is required.

Specification;

Electric Only

Curtain Slat – CSS90 is constructed from a combination of extruded aluminium links and hinge section. Link spacing is 150mm in line as standard, however a brick bond pattern (no surcharge), 75mm spacing (surcharge) and solid slat profile (surcharge) are also available.

Bottom Slat - Extruded aluminium with reinforcing angle and no seal. Shutter Box - Die cast aluminium end plates with two piece roll formed aluminium casing. Larger sizes (shutters with a curtain weight of approx. 75kg upwards) will be supplied with zinc plated steel end plates.

Guide Rails - Extruded aluminium with box section for fixing / reinforcement and high density 4mm or 7mm pile brush seals. UPH140 guides supplied with 205mm box, UPH240 guides supplied with 250 and 300mm box. UPH250 recommended on wider shutters and for shutters requiring higher security with 250, 300 or 350mm box.



DESIGN

MANUFACTURE

INSTALLATION

0800 542 1041

|

WWW.COMPLETESHUTTERSERVICES.CO.UK